

1.2GHz 20dB Gain With GaAs Power Double Amplifier Module

1. Product profile

1.1 General description

High dynamic range power doubler amplifier module operating at a supply voltage of 24VDC in an SOT115 package, using a cascaded power doubler GaAs MMIC , matching with SMT transformer at input and output port adding ESD and surge protective devices.

CAUTION



This device is sensitive to Electro Static Discharge (ESD). Therefore care should be taken during transport and handling.

1.2 Features and benefits

- Excellent linearity
- Low noise
- Ultra-low CSO/CTB/XMOD
- Rugged construction
- High reliability

1.3 Applications

- CATV systems operating in the 40MHz to 1.2GHz frequency range.

1.4 Quick reference data


Bandwidth 40MHz to 1.2GHz; $V_B = 24\text{ V}$; $T_{mb} = 30\text{ }^\circ\text{C}$; $Z_S = Z_L = 75\ \Omega$.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	$f = 50\text{MHz}$	19.5	20.0	21.0	dB
		$f = 1.2\text{GHz}$	20.5	-	-	dB
I_{tot}	total current	$V_B = 24\text{ V}$	420	440	460	mA


2. Pin information

Pin	Description
1	input
2	common
3	common
5	+ V_B
7	common
8	common
9	output

Simplified Outline



Graphic Symbol



3. Operating conditions

3.1 Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134) (TA = +25°C)

Parameter	Symbol	Min	Max	Unit
Supply Voltage	V _B	-	25	V
Input Voltage [1]	V _i	-	65	dBmV
Operating Case Temperature	T _c	-20	+90	°C
Storage Temperature	T _{stg}	-40	+100	°C

[1] In case of single tone

3.2 Recommended operating conditions (Z_S = Z_L = 75 Ω)

Parameter	Symbol	Test Conditions	MIN	TYP	MAX	Unit
Supply Voltage	V _B		23.0	24.0	24.5	V
Operating Case Temperature	T _c		-20	+30	+80	°C

4. Electrical characteristics


(T_c = 30±5°C, V_B = 24 V, Z_S = Z_L = 75 Ω)

Parameter	Symbol	Test Conditions	MIN	TYP	MAX	Unit
Power Gain	G _p	f = 50MHz	19.5	20.0	21.0	dB
Gain Slope	SL	f = 50MHz to 1.2 GHz	1.0	1.5	2.5	dB
Gain Flatness	FL	f = 50MHz to 1.2 GHz	-	-	±0.5	dB
Noise Figure	NF	f = 1GHz	-	5.0	5.5	dB
Operating Current	I _B	V _B =24VDC, RF OFF	420	440	460	mA
Composite Triple Beat	CTB	98 channels, V _o = 48dBmV at 743.25 MHz, flat output level across the band	-	-70	-	dB
Cross Modulation	XM		-	-68	-	dB
Composite 2nd Order Beat	CSO		-	-72	-	dB
Input Return Loss	S ₁₁	f = 40 to 700MHz	16	-	-	dB
		f = 700MHz to 1.2 GHz	16	-	-	dB
Output Return Loss	S ₂₂	f = 40 to 700MHz	16	-	-	dB
		f = 700MHz to 1.2 GHz	16	-	-	dB

5. Package outline

Rectangular single-ended package; aluminum flange; 2 vertical mounting holes; 2 x 6-32 UNC and 2 extra horizontal mounting holes; 7 gold-plated in-line leads.

SOT115-A



UNIT: mm